

# DEFY MARINE SEAL WOOD DOCK CLEANER

## PRODUCT NAME

### DEFY Marine Seal™ Wood Dock Cleaner

MANUFACTURER: SaverSystems  
Richmond, IN 47374  
800-860-6327  
Fax 765-935-4999  
www.defyinfo.com

## DESCRIPTION

**DEFY Marine Seal™ Wood Dock Cleaner** is an environmentally friendly product that safely cleans, brightens, and restores the natural beauty of exterior wood. This product is also an excellent cleaner for exterior vinyl, aluminum, fiberglass and concrete surfaces. Unlike chlorine bleach based cleaners, DEFY Marine Seal™ Wood Dock Cleaner is biodegradable and will not harm wood fibers, grass, plants or marine life. DEFY Marine Seal Wood Dock Cleaner is a powdered concentrate that is mixed with water.

## USES

DEFY Marine Seal™ Wood Dock Cleaner removes dirt, grime, mildew stains, previous coatings (not paint) and weathered graying from horizontal and vertical wood surfaces. DEFY Marine Seal™ Wood Dock Cleaner is recommended for surface preparation prior to application or reapplication of clear finishes and stains (*for best results use DEFY Marine Seal™ Wood Dock Stain*).

## BENEFITS

- Removes Dirt, Grime, Mildew & Graying Wood
- Contains No Acid Or Chlorine Bleach
- Safe For Plants And Marine Life
- Biodegradable
- Environmentally Friendly For "Clean Marinas"

## DIRECTIONS FOR USE

Use 6 ounces (3/4 cup) of DEFY Marine Seal™ Wood Cleaner powdered concentrate with each gallon of water.

NOTE: DEFY Marine Seal Wood Cleaner will darken redwood and some types of cedar. Apply cleaner in a test area to insure proper results prior to proceeding on the entire project.

**STEP 1: MIX:** Mix with water and stir thoroughly until powder is mostly dissolved. Powder dissolves faster in warm water. Solution should be used within six hours of mixing.

### STEP 2: APPLY:

**Horizontal Surfaces:** Dampen surface with water before application. Apply DEFY Marine Seal Wood Dock Cleaner solution with sprayer, brush, or mop, working on small areas, (20-30 sq. ft.) at a time.

**Vertical Surfaces:** Dampen surface with water before application. Apply with a sprayer working on small areas at a time. Begin at the bottom and work to the top.

**STEP 3: BRUSH:** Horizontal Surfaces: Let solution stand approximately 15-20 minutes, keeping area wet with additional DEFY Wood Cleaner solution. Thoroughly scrub with a stiff, short bristle broom or brush.

**Vertical Surfaces:** Let solution stand approximately 15-20 minutes, keeping surfaces wet with additional solution. Thoroughly scrub with a stiff, short bristle broom or brush working from bottom to top. DEFY Wood Cleaner will open wood pores and some raising of wood fibers may occur.

**STEP 4: RINSE:** Rinse thoroughly with water from hose or pressure washer using lowest pressure that cleans without damaging the wood. Repeat steps 2-4 on next small area. Rinse cleaned area of vertical surfaces to avoid streaking as work progresses. Allow wood surfaces to thoroughly dry before applying SaverSystems water repellent wood finishes. Heavily weathered or soiled surfaces may require a second application.

**Coverage:** One gallon of DEFY Wood Cleaner cleans and restores 100-200 square ft. depending on wood porosity.

**STEP 5: NEUTRALIZE:** While still wet after cleaning the entire project, neutralize wood by using DEFY Wood Brightener. This is an essential step before staining.

## CAUTIONS

Contains sodium carbonate peroxyhydrate. Do not mix with chlorine bleach or other chemicals. Store in original container only. Sweep up spills and flush down drain. Contact with combustible organic materials may cause fire. Accumulation of product on ladders, scaffolding, decks, etc., may result in a slippery surface. Avoid contact with eyes and mucous membranes and prolonged contact with skin.

**First Aid:** In case of eye contact, flush with water for 15 minutes and get prompt medical attention. If swallowed, give milk or water. Do

not induce vomiting. Call a physician immediately.

## LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed, or implied. SaverSystems warrants this product to be free from manufacturing defects.

SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product has been applied. This warranty does not include the cost of labor for application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages so this limitation or exclusion may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

## PACKAGING

DEFY Marine Seal Wood Dock Cleaner is available in 2.25 lb. recyclable plastic containers. The 2.25 lb. container of concentrate will make 6 gallons of DEFY Marine Seal Wood Dock Cleaner.

## TRANSPORT AND STORAGE

DEFY Marine Seal Wood Dock Cleaner is not considered hazardous under Department of Transportation regulations. Do not stack pallets. Store in cool, dry area.